

S-Radio 100 / 5 mm

S-Radio 100 / 5 mm is a wireless temperature data logger from -40°C to 140°C (calibration from 25°C to 140°C) with 100 mm length, 5 mm diameter external probe on a 13 mm cone base (base height is not counted for probe length), managed with Windows software and USB interface. **Battery is user replaceable** and the data logger is **provided with an Accredia** (NIST equivalent) **traceable certificate** on 4 points.

Thanks to S-Radio **process data can be viewed in real time** on PC screen along with progressive lethality (pasteurisation units) values. Alarms can be set on temperature and lethality value itself. With P-Radio you can act in real time on the process, knowing the thermal curve at the core of the product.

The other versions of the data logger are:

- S-Radio: with rigid probe of different lengths
- S-Radio Flexible: with flexible cable probe and rigid probe at the end
- S-Radio Bendable: with semi-rigid metal bendable probe and rigid probe at the end

The version for up to 100°C is available too, along with flexible, bendable versions.

It is part of a series of data loggers divided in P-Radio (up to 100°C) and S-Radio (up to 140°C). They require an interface for PC connection: DiskInterface HS, Multibay. For real time data the USB Radio Receiver is needed as well.

There are also other models of high temperature data loggers, for pressure and humidity too.

Main features

- With thicker probe to be more robust
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- **Replaceable battery (software shows battery status)**
- **Real time data transmission**, no installation requested
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -40°C** (order extra calibration points)

Plus

- High accuracy and precision, food grade, probes of different size
- Very easy to deploy in any type of package with the fastening system
- Fast response time thanks to the 3 mm diameter probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)
- Knowing the thermal curve in real time will allow to act immediately saving time, money and increasing the quality of the product

The system

The system is made up by:

- S-Radio temperature data logger
- DiskInterface HS or Universal Multibay
- USB Radio Receiver or Ethernet Receiver (for Process Monitor Pro software only)



Applications



Food & Beverages



Sterilisation



Pasteurisation



Laboratories



Warehouses



Pharmaceutical



Healthcare



Validation

- SPD software, TS Manager software (compatible with the FDA 21 CFR Part 11 regulation) or Process Monitor software

Accessories

- SPD
- TS Manager
- Process Monitor Lite
- Process Monitor Pro
- DiskInterface HS
- Universal multibay
- USB Radio Receiver
- Ethernet radio receiver
- 4-20 mA receiver
- Locking bolt
- Fastening system
- Teflon protective tube
- P-Radio, S-Radio battery kit

Technical specifications

Dimensions	76 h X 30 Ø (mm)
Probe dimensions	Probe base dimensions 13 h X 15 Ø (mm) - Probe 100 l X 5 Ø (mm)
Weight	76 gr
Materials	Stainless steel AISI316L, PEEK
Temperature range	-40°C ÷ +140°C
Standard calibration points (temperature)	25/50/75/100/125/140°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +140 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,1 °C (within the calibration range)
Memory (n. of acquisitions)	121.171
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+3.800.000 acquisizioni ad 1 secondo in continuo (tempo stimato @ 25°C. La vita della batteria è più breve a basse ed alte temperature)
Software&Mobile App	SPD, TS Manager, Process Monitor
Accessories	DiskInterface HS, Multibay universale, USB Radio Receiver, Ethernet receiver, 4-20 mA receiver



Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

